NMW-14B Cast Iron Ball Valve Flanged Ends

Description

NETA Cast Iron Ball Valve
– Full Bore
– Three Piece Design
– With Stainless Steel (AISI – 410) Ball and Blow-out Proof Stem
– Teflon (PTFE) Body Seat Rings and Seals
– Lever Operated
– Flanged Ends to BS-10 Table 'F'

Test Pressure

Test Pressure : 300 PSIG Hyd.

Certification

Works Test Certificate can be issued, if required.

Application : Water, Oil, Air

HSN : 84818010

Materials

PNo.	Part	Nos.	Material	Standard
1	Stem	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI – 410
2	Lever Nut	1	M.S.	IS:1367
3	Lever	1	M.S. / SG Iron	IS:226 / IS:1865 Gr.400/15
4	Gland	1	S.S. 13% Cr.	ASTM A182 Gr.F6a
5	Gland Packing Ring	–	Teflon	PTFE / BS:EN 12086-1
6	Gasket	2	C.A.F.	IS:2712
7	Body Seat Ring	2	Teflon	PTFE / BS:EN 12086-1
8	Ball	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI – 410
9	Body	1	C.I.	IS:210 Gr.FG200
10	Studs	To Suit	M.S.	IS:1367
11	Nuts	To Suit	M.S.	IS:1367
12	Connector	1	C.I.	IS:210 Gr.FG200

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	L ±1.5	H App.	W App.
1/2	15	135	78	158
3/4	20	138	85	178
1	25	146	90	178
1.1/4	32	170	110	195
1.1/2	40	174	115	230
2	50	200	120	250
2.1/2	65	212	135	300
3	80	220	143	300
4	100	265	170	300