13 Bronze Combined Cock & Feed Check Valve Flanged Ends

Description

- NETA Bronze Combined Cock and Feed Check Valve
- Flanged BS-10 Table ‘F’ Ends



Test Pressure

Max. BOP : 150 PSIG
Max. Working Temperature : 220°C
Test Pressure : 300 PSIG Hyd.

Certification

IBR Test Certificate in FORM III-C duly signed by the Director of Boilers, Punjab is provided.

Application : Steam, Water

HSN : 84818020

Materials

PNo.	Part	Nos.	Material	Standard
1	Plug	1	Bronze	IBR 282[a][iv] Gr.B
2	Gland	1	Bronze	IBR 282[a][iv] Gr.B
3	Packing	–	Flexible Pure Graphite	–
4	Cover	1	Bronze	IBR 282[a][iv] Gr.B
5	Disc	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI – 410
6	Spring	1	Carbon Steel	IBR 307
7	Body Seat Ring	1	S.S. 13% Cr.	ASTM A182 Gr.F6a / AISI – 410
8	Body	1	Bronze	IBR 282[a][iv] Gr.B
9	Bolts	2	M.S.	IS:1367

Dimensions

Nominal Size (Inches)	Nominal Size (mm)	L App.
1/2	15	107
3/4	20	120
1	25	136.5
1.1/4	32	158.5
1.1/2	40	166
2	50	202
2.1/2	65	210

