

NMW-16C S.S. Investment Casting Ball Valve Flanged Class-150

Description

- NETA Investment Casting S.S. (CF8) Ball Valve
- Design Standard: As per BS 5351
- Full bore, three piece design
- Lever Operated
- Flanges as per ASME B 16.5 Class-150

Certification

Our Works Test Certificate can be issued, if required.

Application : Water, Oil, Air

HSN : 84818010



Materials

PNo.	Part	Nos.	Material	Standard
1	Body	1	CF8	ASTM A351
2	Side Flanges	2	CF8	ASTM A351
3	Ball	1	S.S. 18% Cr.	AISI-304
4	Stem	1	S.S. 18% Cr.	AISI-304
5	Body Seat Ring	2	Teflon	ASTMD3294
6	Gland Packing	4	Teflon	ASTM D3294
7	Stud & Nut	4 & 8	Alloy Steel/H.T Steel	ASTM D3294
8	Gland	1	S.S. 18% Cr.	AISI - 304
9	Lever	Carbon Steel	S.S./M.S.	S.S./M.S.
10	Lever Nut	1	S.S. 18% Cr.	AISI-304
11	Gasket	2	Teflon	ASTMD3294

Dimensions

Nominal Size (mm)	F/F	B	C	PCD	FT
15	108	89	12.5	60.5	10
20	117	98.5	19	70	10.5
25	127	108	25.4	79.5	11.2
40	165	127	38	98.5	14.5
50	178	152.5	51	120.5	16
65	190	178	64	140	17.5
80	203	191	76	152.5	18
100	229	229	102	190.5	22
150	267	279	150	241.5	25.5

